

**§ 428-59. Numbering of buildings.**

- A. The owner, lessee/tenant or agent of an owner or lessee/tenant shall place or cause to be displayed upon each improvement controlled by him, the number or numbers assigned to the lot or unit by the GIS Map.
- B. The numbers used shall be Arabic, not less than three inches in height, made of durable and clearly visible material, and shall be legible and maintained in good order at all times. Roman numerals or script may supplement this requirement but shall not be a substitute for compliance. All numbers posted shall be of reflective material or of sufficient visual contrast to the background material to be easily discernible at night with the aid of an emergency vehicle spotlight.
- C. The numbers shall be conspicuously placed on the improvement facade parallel to the street immediately above, or within 10 feet of either side of the main entrance to the improvement or over the garage door so that the number can be plainly read from the center line of the street in daylight by a person possessing normal vision.
- D. Whenever any improvement is situated more than 50 feet from the street line, the designated number shall be displayed as provided in Subsection C, but the numerals shall be at least five inches in height.
- E. If the number would not be visible due to the orientation setback or other features of the site if displayed as provided above, then the number shall be placed near the walk, driveway or entrance to such improvement and upon a gate, post, or fence so as to be easily discernible from the center line of the street. Such a display shall be no closer than 10 feet to the curblin nor further away than 30 feet from the curblin. The bottom of such a display shall be no less than 30 inches above the level of the ground, nor shall the top of such a display be more than eight feet above the ground.